

A22 INDUSTRIAL DUST COLLECTOR



The A22 single phase dust collector is the perfect partner for our smaller range of single phase grinders and scarifiers.

The A22 is the ultimate compact unit for surface preparation machines and general cleaning applications.

The standard Class M filter offers exceptional surface area and filtration, the optional HEPA filter is classified to the highest rating H14.

The A22 features the ENDLESSBAG safe bagging system for easy containment and disposal of material.

Now fitted with a new reverse pulse filter cleaning system ensuring continuous reliable performance under the hardest conditions.

FEATURES

- 100% steel construction for long service life
- Two motors
- Class M primary filter with optional HEPA filter
- Complete with 40mm tool kit
- Reverse pulse filter cleaning system for performance and long service.
- Low noise level

APPLICATIONS

- Perfect partner for smaller surface preparation equipment such as TFP200 scarifier, TCG hand grinders and TCG250 single head grinder
- Also ideal for use with many other smaller types of construction equipment with options for dust extraction
- General cleaning of fine dust in many other industries



Use with TFP200 Floor Scarifier



ENDLESSBAG Bag System



Use With TCG250 Floor Grinder

KEY CONSUMABLES & ACCESSORIES

Image	Part Number	Description
	303.5750	D.40 Chromed Bend Included as standard
	303.5630	D.38 Black Flexible Hose (5mt) + 50/40 Flex Connection (Left Thread) + D.40 PVC Connection Included as standard
	303.5482	40mm threaded hose connection to 50mm machine connection 2 Included as standard
	303.5477	40mm threaded hose connection to 40mm machine connection 1 Included as standard
	303.5755	D.40mm 400 Dust Brush Included as standard
	303.5485	D.40 PVC Brush
	303.5760	D.40 Rubber Cone Section with Connection
	303.5770	ENDLESSBAG Bags Pack of 4 x 20m tubes

TECHNICAL DATA

Model	Part Number	Output Power (Hp - kW)	Output flow (M ³ per h / Lt per sec)	Vacuum Rate (mm. H ₂ O)	Filter Type	Filter Efficiency	Filter Surface Area	Suction Inlet (Ø)	Noise Level (Db (A))	Dimensions (cm)	Weight (kg)
A22 Bin 110v Class M	303.4100	31 - 2.3	360 - 100	2500	Class M	99.93%	3m ²	50	76	62 x 53 x 107	35
A22 Bin 230v Class M	303.4105	31 - 2.3	360 - 100	2500	Class M	99.93%	3m ²	50	76	62 x 53 x 107	35
A22 EB 110v Class M	303.4103	31 - 2.3	360 - 100	2500	Class M	99.93%	3m ²	50	75	53 x 56 x 130	35
A22 EB 230v Class M	303.4107	31 - 2.3	360 - 100	2500	Class M	99.93%	3m ²	50	75	53 x 56 x 130	35
A22 EB 110v Type H	303.4104	31 - 2.3	360 - 100	2500	HEPA	99.995%	4.9m ²	50	75	53 x 56 x 130	35
A22 EB 230v Type H	303.4108	31 - 2.3	360 - 100	2500	HEPA	99.995%	4.9m ²	50	75	53 x 56 x 130	35